



## i-7051D

16 Channel Digital Input Module

### Digital Inputs

Channels	16
Input Type	Dry Contact(Source), Wet Contact(Sink, Source)
Dry Contact	Off Voltage Level : open On Voltage Level : close to GND
Effective Distance	500M max. for Dry Contact
Wet Contact	Off Voltage Level : +4V max. On Voltage Level : +10V to +50V
Input Impedance	10K Ohms, 0.5W
Counters	channels : 16
	Max. Counters : 16-bit (65535)
	Max. Input Frequency : 100Hz Min. Pulse Width : 5ms
Over-Voltage Protect	70VDC
Photo-Isolation	3750Vrms
<b>Interface</b>	
Interface	RS-485
Format	N, 8, 1
Baud Rate	1200 ~ 115200bps
<b>LED Display</b>	
1 LED as Power/ Communication indicator	
16 LEDs as Digital Input indicators (for i-7051D)	
<b>Power</b>	
Input Voltage Range	10~30VDC
Power Consumption	0.6W (i-7051) / 1.5W (i-7051D)
<b>Environment</b>	
Operating Temperature	-25 to 75°C
Storage Temperature	-40 to 85°C
Humidity	5 to 95%, non-condensing

## Industrial Weighing Systems

9 Richmond St. Picton, ON Canada K0K 2T0

Ph: 613-786-0016 Cell/Local: 613-921-0397 Fax: 613-476-5293

E-mail [info@iwsystems.ca](mailto:info@iwsystems.ca) Website: [www.iwsystems.ca](http://www.iwsystems.ca)